

EMMVEE IS INDIA'S FIRST INTEGRATED SOLAR SOLUTIONS COMPANY, WITH 30 YEARS OF EXPERTISE IN DEVISING HIGHLY INNOVATIVE AND EFFICIENT SOLAR POWER SOLUTIONS, FROM SOLAR WATER HEATING SYSTEMS TO PHOTOVOLTAIC MODULES AND SOLAR WATER PUMPS.

Since our inception in 1992, we have dedicated ourselves to developing smart and innovative solar energy solutions using cutting edge technology. As always, our promise is to maintain enviable standards of excellent quality, timely delivery and reliable support to our customers as they explore and adopt environmentally friendly solar power solutions.

Today, we are proud of our robust presence in some of the most pioneering green energy projects across Indic and Europe. Our path-breaking photovoltaic modules have provided valuable and sustainable alternative power solutions in the field for over 15 years, and we continue to innovate with our new range of higher WP modules that combine exceptional quality and unbeatable efficiency.

Our goal is simple: to provide clean and reliable energy that saves our natural resources and reduces our carbon footprint, while ensuring that our diverse range of domestic and commercial solar power-related products and services always keep the needs of our customers at the forefront.

FEATURES



AR COATED HIGH TRANSMISSION GLASS



MC4 COMPATIBLE CONNECTORS



PID RESISTANCE



ANODISED
ALUMINIUM FRAME



MECHANICAL LOAD OF 5400 Pa

BENEFITS



LOW LCOE, FASTER PAYBACK PERIOD



BEST IN CLASS EFFICIENCY



MULTI-BUS BAR TECHNOLOGY FOR BETTER CURRENT COLLECTION



LOWEST GUARANTEED FIRST YEAR AND ANNUAL DEGRADATION



WELL-COMPOSED COMPONENTS STRESS TO REDUCE MICRO CRACKS

TECHNICAL SPECIFICATION

120 CUT CELL BLACK BACK SHEET MODULE

Electrical data at 1000W/m², 25°C and A.M 1.5(STC in accordance with IEC 60904-3)

MODEL NAME	E440HCM120-B	E445HCM120-B	E450HCM120-B
RATED POWER AT STC	440	445	450
POWER TOLERANCE	+5W	+5W	+5W
MODULE EFFICIENCE AT STC	20.28%	20.51%	20.74%
OPEN CIRCUIT VOLTAGE - VOC(VOLTS) (±10%)	41.44	41.46	41.56
SHORT CIRCUIT CURRENT - ISC (AMPS) (±10%)	13.55	13.75	13.81
MAX POWER VOLTAGE - VPM (VOLTS)	34.21	34.28	34.31
MAX POWER CURRENT - IPM (AMPS)	12.87	12.99	13.12
AT LOW IRRADIANCE (200W/M², 25°C AND AM1.5) THE MODULE YIELDS AT LEAST 95% OF THE STC EFFICIENCY.			

Test uncertainty for Pmax ±3%

Thermal data

TEMPERATURE COEFFICIENT OPEN-CIRCUIT VOLTAGE	-0.28%/°C
TEMPERATURE COEFFICIENT SHORT CIRRCUIT CURRENT	0.05%/°C
TEMPERATURE COEFFICIENT RATED POWER	-0.39%/°C
NOCT (NORMAL OPERATING CELL TEMPERATURE)	45°C±2°C

Mechanical data


NUMBER OF CELLS AND CELL TYPE	120 MONO PERC SOLAR CELLS (182mm X 91mm)
DIMENSIONS: (L X W X H)	75.32 inch X 44.65 inch X 1.38 inch
WEIGHT	52.91 Pounds
FRONT GLASS	3.2 mm HIGH TRANSMISSION, SOLAR GLASS
EMBEDDING	EVA
BACK SHEET	BLACK BACK SHEET
JUNCTION BOX	3 SPLIT JUNCTION BOX IP68
NUMBER OF BYPASS DIODES	3
CABLES	4mm² SOLAR CABLES, LENGTH 1200±10mm
CONNECTORS	MULTI CONTACT OR STAUBLI OPTION AVAILABLE

Permissible operating conditions

OPERATING TEMPERATURE RANGE	-40°C TO 85°C
MAX.SYSTEM VOLTAGE	1500V DC
MAXIMUM SNOW LOAD CAPACITY	5400PA
RESISTANCE AGAINST HAIL	MAX Ø24 MM WITH IMPACT SPEED OF 83KM/H
PROTECTION CLASS AGAINST ELECTRICAL SHOCK	II .
MAXIMUM REVERSE CURRENT	25 A

Warranty

PRODUCT WARRANTY	12 YEARS
PERFORMANCE WARRANTY	25 YEARS
ANNUAL DEGRADATION	1ST YEAR DEGRADATION, 2%, FROM 2ND YEAR
	0.55% ANNUAL DEGRADATION.





MONO-FACIAL MODULE

Positive power tolerance +5W

- Half Cut Cell Technology
- Best Warranty
- 10BB instead of 5BB
- Enhanced Mechanical Load
- · Higher lifetime Power Yield
- Multi Busbar Technology
- Longer Life-time Power Yield
- PID Resistance
- Excellent Low-light Performance
- Higher Power Output























EMMVEE PHOTOVOLTAIC POWER PRIVATE LIMITED