

ITEM NO.	DESCRIPTION	QTY.
2	POST, 1.25" OD X 4", 6063-T5/6063-T6, MILL	1
3	WASHER, SEALING, 5/16" ID X 1-1/4" OD, EPDM BONDED SS	1
4	FLASHING, REPLACEMENT TILE, W-TILE, .625" CONE, ALUMINUM, MILL	1
5	COLLAR, COUNTER FLASHING, 1-1/4" ID EPDM	1
6	CAP SCREW, HEX HEAD, 5/16"-18 X 1" UNC- 2A, NYLON PATCH, W/CAPTIVE WASHER, 1"OD, 18-8 SS	1
7	CAP SCREW, SERRATED FLANGE, HEX HEAD, 5/16"-18 X 1" UNC-2A, GRADE 8, MAGNI 525	1

AVAILABLE IN MILL, AND BLACK FINISHES

## Quick Mount PV®

TITLE:

QMTR-W4: TILE REPLACEMENT, W-TILE, 4" POST

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL± 1/8
TWO PLACE DECIMAL ±.19
THREE PLACE DECIMAL ±.094

SIZE DRAWN BY: JPW REV

A DATE: 1/28/2020 8

SCALE: 1:5 WEIGHT: 1.27 SHEET 1 OF 1

<sup>†</sup> 4

WRITTEN PERMISSION OF QUICK MOUNT PV IS PROHIBITED. COPYRIGHT © 2020 QUICK MOUNT PV

3

1