

RSTC Enterprises, Inc.
Eau Claire, WI 54703



Outdoor Photovoltaic Enclosures 0799 Series

Composition/Cedar Roof System

ETL listed and labeled

Report # 3171411PRT-002 Revised May, 2018

- UL50 Type 3R, 11 Edition Electrical equipment enclosures
- CSA C22.2 No. 290 Nema Type 3R
- Conforms to UL 1741 Standard
- 1000 VDC/180 amps
- 480 VAC/60 amps
- 20 year limited warranty

0799 Series Models		
	Ground Type	Ground Wire Size
0799-2	2 Position Ground	2/0-14
0799-5	5 Position Ground	14-6
0799-D	Dual Ground	14-8

Models available in Grey, Black or Stainless Steel

Basic Specifications

Material options:

- Powder coated, 18 gauge galvanized 90 steel (1,100 hours salt spray)
- Stainless steel

Process - Seamless draw (stamped)

Flashing - 15.25" x 17.25"

Height - 3"

Cavity - 255 Cubic inches

Approximate weight - 9.2lb

Base Plate:

- Fastened to base using toggle fastening system
- 5 roof deck knockouts
- Knockout sizes: (3) .5", (1) .75" and (1) 1"
- 8", 35mm slotted din rail
- Ground Block

Passthrough and combiner kits are available for either AC or DC applications.

